

DATA SHEET.

SPRAY EXTRACTION MACHINE.

SX 344




G. Staehle GmbH u. Co. KG
Mercedesstrasse 15
D 70372 Stuttgart
Telefon +49 (0) 7 11/95 44-950
Telefax +49 (0) 7 11/95 44-941
info@columbus-clean.com
www.columbus-clean.com

CLEAN IS QUALITY **columbus**

REMOVE SPOTS, CLEAN SURFACES. PRODUCTIVITY INVERSES WITH EFFICIENCY.

SX 344

- ❶ The spray extraction method machine for stain removal and deep cleaning of textile floor coverings, upholstery and hard floors are very effective. Compact and easy to operate.
- ❷ The top-quality two-level suction motor sucks up dirt particles with 295 mbars of vacuum pressure. The surfaces dry thoroughly and can be used again soon.
- ❸ This model have modular construction so that emptying the tank for dirty water is easy, for thorough cleaning as well as quick and inexpensive maintenance.
- ❹ Robust construction with two separate tanks made of high density polyethylene.
- ❺ Filters and seals can be removed without tools.
- ❻ The tank for the dirty water has a transparent lid allowing inspection of loosened dirt during operation.
- ❼ The high-performance professional appliance with 9 bars of spray pressure for medium-sized furnished surfaces.
- ❽ High-quality attachments are series standard: aluminium spray lance with ergonomic vertically adjustable grip and five-metre spray-suction hose.
- ❾ Optional: the power brush roller with rotating brush turns the SX 344 into a scrubber dryer for carpets (see illustration).



Power brush roll function



SX 344

L x B x H	380x500x780 mm
Working width	300 mm
Spray volume	4,5 l/min
Spray pressure	9 bar
Weight	24 kg

ELECTRICAL DATA

Power max.	1580 W
Mains cable	10 m

TANK

Solution tank capacity	30 l
Recovery tank capacity	30 l

SUCTION

Low pressure max.	295 mbar
Air flow max.	45 l/s

STANDARD EQUIPMENT

Floor tool	Aluminium
Tube	5 m